

Horizontal Mount Side Lights

2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material:	Zinc Alloy Top with Black or White Base,
Finish:	Chrome Plated or White Powder Coated
Dimensions:	Length: 3-1/4", Width: 2-1/4", Height: 1-1/2"
Screw Size:	#6
Contacts:	Gold Plated
Voltage:	12V (Bulb Included)
Wattage:	10 watts (each light)
Amperage:	.80 amps (each light)



Fig. 0228
Chrome



White

Finish	Retail Pkg.*	OEM Bulk Pkg.*
Chrome	0228DP0CHR	0228000CHR
White	0228DP0WHT	0228000WHT

*Sold in pairs.



1-mile (USCG 1nm) Certified

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

Material:	Polymer
Finish:	Black
Dimensions:	Base: 1-1/8" x 3", Height: 1-7/8"
Mount:	Fig. 1601 - Normal "Base-Down" Fig. 1602 - Inverted "Base-Up"
Screw Size:	#8
Voltage:	12V (Bulb Included)
Wattage:	10 watts (each light)
Amperage:	.80 amps (each light)
Use:	Great for Pontoon Boats

Fig. 1601



Fig. 1602

Mount	Retail Pkg.*	OEM Bulk Pkg.*
Base Down	1601DP0BLK	1601000BLK
Base Up	1602DP0BLK	1602000BLK

*Sold in pairs.



Note: The above lights can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.

Spare Parts Information

Fig. 0228:

Green Lens: 0228DPGLNS.
Red Lens: 0228DPRLNS.
Bulbs (2 per card): 0071DP0CLR.
Black Base w/Socket Assy: 022700099A.
White Base w/Socket Assy: 0227W0099A.



Fig. 0228



Fig. 0071DP0CLR

Figs 1601 & 1602:

Red Lens Only: 0298DPRLNS,
Green Lens Only: 0298DPGLNS
Red Light Only: 1601R00BLK, 1602R00BLK
Green Light Only: 1601G00BLK, 1602G00BLK
Bulbs: 0071DP0CLR
Base w/Socket Assembly: 0139000BLK



Fig. 0298



Fig. 0071DP0CLR